

## HI 10500

<b>Rated Line Pull</b>	4763 Kgf
<b>Gear Train</b>	Planetary
<b>Gear Ratio</b>	6:1 (low gear) / 1:1 (high gear)
<b>Motor</b>	293 CC
<b>Cable</b>	Φ9.525 mm X 30.5 m (length)
<b>Directional Control</b>	12V Solenoid 3 way (also available in 24V)
<b>Valve</b>	Integrated (max. rated flow 13.3 lit/min) draws 2 amps
<b>Control switch</b>	Remote Switch, 3.7 m
<b>Hoses</b>	Two hoses (1.5m and 2.1m) steel braid high pressure, 3000 PSI (207 bar) rating. Uses size 6 JIC swivel
<b>Drum size</b>	Φ63.5 mm X 228.6 mm (long)
<b>Bolt pattern</b>	254 mm X 114.3 mm (4 bolts, 3/8")
<b>Shipping weight</b>	47 Kgs

### Performance Specs

3.5 GPM (13.3 lit/min) @ 1500 PSI (103.4 bar)				
<b>Layer</b>	1	2	3	4
<b>Line speed - low gear (mpm)</b>	1.72	1.96	2.26	2.62
<b>Rated pull -low speed(Kgf)</b>	4763	3856	3357	2903
<b>Line speed - high gear(mpm)</b>	9.45	10.97	12.8	14.63
<b>Rated pull - high speed(Kgf)</b>	726	590	544	454

## H 10500

<b>Rated Line Pull</b>	4763 Kgf
<b>Gear Train</b>	Planetary
<b>Gear Ratio</b>	6:1 (low gear) / 1:1 (high gear)
<b>Motor</b>	293 CC
<b>Cable</b>	Φ9.525 mm X 30.5 m (length)
<b>Drum size</b>	Φ63.5 mm X 228.6 mm (long)
<b>Bolt pattern</b>	254 mm X 114.3 mm (4 bolts, 3/8")
<b>Shipping weight</b>	42 Kgs

### Performance Specs

3.5 GPM (13.3 lit/min) @ 1500 PSI (103.4 bar)				
<b>Layer</b>	1	2	3	4
<b>Line speed - low gear (mpm)</b>	1.72	1.96	2.26	2.62
<b>Rated pull -low speed(Kgf)</b>	4763	3856	3357	2903
<b>Line speed - high gear(mpm)</b>	9.45	10.97	12.8	14.63
<b>Rated pull - high speed(Kgf)</b>	726	590	544	454